



Absco Sealer Oil n H2O Wood Floor Sealer Technical Data Sheet



PRODUCT DESCRIPTION

Absco Sealer, is an ambering wood floor sealer featuring Oil n Water technology. When using under oil modified finish products, the sealer must be completely dry. Sealer can be applied directly on stained wood surfaces, or on raw wood. **DO NOT USE OVER POLYURETHANE, LACQUER OR OTHER SEALED SURFACES.** No thinning required.

RECOMMENDED USES:

Excellent for sealing most interior wood surfaces including floors, doors, cabinets, and furnitures.

TYPICAL PROPERTIES

Color in Container	Amber color(dries clear)
Solids Content	25+/-1%
Chemical Resistance	Excellent
VOC	VOC does not exceed 275 grams/liter
Flash Point	198°F
Pot Life	Unlimited in unopened container
Dry Time	2 hours with good conditions
Clean Up	Water
Application method	T-Bar applicator, Synthetic waterborne applicator, Nnylon brush.
Coverage	550-650 sq. feet per gallon.

Proper surface preparation is essential to achieve a high quality finish. Read the MSDS sheet and wear proper protection, which may include gloves, eye protection, and/or other protective devices.

Surface Preparation: New or Newly Sanded Floors or Wood Surfaces:

Prepare the floor according to NWFA or NOFMA accepted standard. The final pass before application of sealer should be a #100 to #150 grit screen pad or sandpaper. Remove dust completely by sweeping, vacuuming and wiping the floor or work surface with a lint free cloth lightly dampened with water. The floor or work surface and room temperature should be at least 65°F.

APPLICATION: Apply sealer using standard water based finish techniques. Applicator should be slightly damp with finish before starting. Pour sealer onto floor 4" strip along the starting wall. Apply the sealer with the grain of wood. Pull the applicator towards you holding the applicator at a slight "snowplow" angle. Remember keep a wet edge as you work. When you reach the end wall, pull the applicator in a sweeping motion, without lifting it from the floor. Feather turn, and gently touch any missed spots. Apply at recommended coverage. Screen the floor or work surface with any of the following: #100 to #150 screen disc, #180 grit sand paper, or maroon pad prior to application of first top coat. Don't over sand between coats.

Drying Time: Absco Sealer should be dry to the touch in 1 hour. Allow minimum of 2 hours before screening and for the topcoat to be applied. Heavy finish application, high humidity or lack of airflow will extend drying times. Under oil, longer dry time maybe needed.

Clean up: Use water to clean brushes and applicators.

absolute coatings, inc.

Wood Finishes for Professionals™

38 Portman Road, New Rochelle, NY 10801 1-800-221-8010 FAX (914) 636-0822 www.lastnlast.com

©2008 Absolute Coatings, Inc. All Rights Reserved



FIRST AID: **If swallowed:** Call physician immediately. **For Skin,** Wash thoroughly with soap and water. **Inhalation:** If affected, immediately seek fresh air. If symptoms persist, get immediate attention. **For eye contact:** Flush eyes with water IMMEDIATELY! Then remove any contact lenses. Continue flushing with water for at least 15 minutes. If irritation persists, get medical attention.

HEALTH AND SAFETY PRECAUTIONS : VAPOR AND SPRAY MIST HARMFUL. MAY CAUSE DIZZINESS, HEADACHE, OR NAUSEA. HARMFUL IF ABSORBED THROUGH SKIN. CAUSES SKIN IRRITATION.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Close container after each use. Use only with adequate ventilation. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Close container after each use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

LEGAL DISCLAIMER

Manufacturer's Warranty: Absolute Coatings, Inc. and its distributors' only obligation shall be to replace such quantity of the product proved to be defective. As a professional product, the user accepts full responsibility for the applicability of this product for their specific use. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, the user shall determine the suitability of the product for the intended use and user assumes all risk and liability whatsoever in connection therewith.