

PALL-X RETARDER

Working time extender for all PALLMANN® waterborne wood floor sealers and finishes.

Description

PALLMANN® PALL-X RETARDER is a working time extender for all PALLMANN® waterborne wood floor sealers and finishes. It is designed to provide optimum flow and leveling in warm and dry conditions.

Note: Optimum application conditions for finishes are 65 – 80°F with 40 – 60% relative humidity. The use of PALL-X RETARDER is recommended when temperatures exceed 80°F and relative humidity drops below 30%.

Technical Data

Packaging: 1 quart plastic bottle

Color: Clear

Stability: Minimum 12 months

Mixing Ratio: Maximum 5% retarder to finish by

volume

Storage: Store between 50-70°F (10-20°C).

Keep from freezing.







PALLMANN I A Brand of Uzin Utz Group Aurora, CO 80011 USA | Phone: 720. 374.4810 pallmann.us@uzin-utz.com I pallmann.us

Directions for Use

- 1. Bring PALL-X RETARDER to room temperature.
- Shake each container of finish vigorously for approximately
 1 minute making sure all ingredients are well mixed. Failing to
 mix any finish product may result in streaking when finish is dry.
 When using PALL-X 98, PALL-X RETARDER must be mixed with
 Component A (finish) before adding Component B (hardener).
- 3. Add a maximum of 5% (6.5 ozs.) PALL-X RETARDER to 1 gallon (128 ozs.) of finish and shake vigorously for 1 minute. The Retarder must be thoroughly mixed with the finish. Important Note: Finish mixed with PALL-X RETARDER should be used within 5 days.

Clean Up

Tools and applicators should be cleaned with water.

Storage

Minimum 12 months in original packaging when stored under normal conditions (50-70°F/10-20°C). Tightly reseal opened containers. Keep from freezing.

Disposal

Dispose of empty containers according to local, state and federal regulations.

Precautions

KEEP OUT OF REACH OF CHILDREN. Keep container closed during storage. Avoid contact with eyes and skin. Avoid breathing vapors. Use only in well-ventilated areas. Use of protective gloves (rubber) and safety glasses is recommended. Non-flammable.

FIRST AID: In case of skin contact, wash thoroughly with soap and water. For eye contact, flush immediately with large amounts of water for at least 15 minutes and obtain medical treatment. If swallowed, obtain medical treatment immediately.

