

ARBORITEC™ Miracle Oil

TWO COMPONENT
WOOD FLOOR OIL FINISH

Arboritec Miracle Oil™ preserves and protects the natural richness and color of wood floors with a rich patina look.

Miracle Oil™ is easy to maintain and repair without re-sanding.

Miracle Oil™ is produced with all natural, renewable and sustainable resources and contains no harmful, toxic chemicals.

Safe for you, and safe for the environment.



- Creates a deep rich, low gloss, natural patina sheen -

- A natural product, no solvents, low VOC -

- Dries fast – fully cured and ready for normal use in 12 hours -

- Easy to repair or restore to original patina sheen -

- Perfect for hand scrapped and rustic wood floors -

- Recoat with an Arboritec waterborne finish if desired -

**IF IT'S NOT ARBORITEC,
IT'S NOT FINISHED!**

ARBORITEC™ Miracle Oil

PRODUCT DESCRIPTION

Arboritec Miracle Oil™ is a 2 component wood floor sealing and finishing oil which provides a very durable protective finish and gives the floor a very rich, natural patina surface. Miracle Oil is quick drying, easy to clean and can be recoated and or repaired without sanding. Miracle Oil is designed to be used as a one coat system for a residential application or a two coat system for commercial high traffic floors. All Miracle Oil base colors can be mixed to create a custom color to your liking.

DIRECTIONS FOR USE

Sand the floor according to accepted industry standards, such as the NWFA™ recommendations. The final cut should be 100 grit. Make sure the surface is dry and free from dust, wax, grease and other contamination. Temperature of the room, floor and Miracle Oil must all be kept the same within the range of 65°F to 80°F. Relative humidity should be between 40% and 60%. Stir components A & B thoroughly and evenly – DO NOT THIN.

APPLICATION

Apply Arboritec Miracle Oil directly to the floor. Pour a puddle approximately 5" in diameter. The puddle should be poured 18-24" away from any walls. Place red polishing pad directly on top of the puddle and buff until the floor does not accept any more oil. Add Miracle Oil as needed to ensure an even coverage for best results. Repeat process when adding a second coat. A newly oiled floor will be fully cured, and ready for regular, normal use in 12 hours.

Trowel method for applying Miracle Oil: Using a stainless steel trowel, apply evenly and thinly to the surface at a rate of 325-550 sq. ft. per liter.

CAUTION! A danger of self-ignition (spontaneous combustion) exists in contact with organic materials (cotton cloths, sawdust, rags etc.). Rags and other organic materials soaked in oil have must be placed into tightly sealed container with water to prevent the risk of fire.

TECHNICAL DATA

Binding Agent	Based on Linseed Oil	Color	Natural, White, Gray, Black, Teak, Brown
Recommended Use	Commercial & Residential	Thinner	Linseed oil
Additional Features	Solvent Free	Odor	Very light, non-offending
Coverage	325 - 550 sq. ft. per liter	Toxicity	Non-hazardous
Dry Time (68° F, RH 55%)	15-30 min after 1st application 2.5 hours after 2nd application	Packaging	1 liter steel can in solid paper tube, including component B hardener
Full Cure	12 hours	Storage	Non-flammable, KEEP FROM FREEZING!
Solids by Volume	Approx. 100%	Shelf life	12 months in unopened original container
Pot Life	12 hours after mixing	Clean Up	Throughly clean all application tools with mineral spirits, right after using
Application Temperature	Between 65°F to 80°F. Do not expose to temp over 100°F	Disposal	Dispose in accordance with local regulations
		Maintenance	For normal maintenance, use Arboritec Wood Floor Cleaner to keep the floor looking its best. To repair worn or damaged areas, use Arboritec Miracle 2™ Maintenance Oil.

**PLEASE READ ALL LABEL INSTRUCTIONS AND MATERIAL SAFETY DATA SHEET BEFORE USING.
FOR PROFESSIONAL USE ONLY! KEEP FROM FREEZING!**



Arboritec USA, Inc.

6200 S. Syracuse Way, Suite 125 | Greenwood Village, CO 80111

Toll Free: 877-416-5972

www.arboritec.com © 04/12 Arboritec USA

